

# FlexiViewer

For Mammography and  
General Radiology



Shown with optional  
film jacket file.

# FlexiViewer

## For Mammography and General Radiology

**For when you screen both mammograms and 14 x 17-inch films.** The film belts on the FlexiViewer support a wide variety of films, from 14 x 17-inch to 18 x 24 cm. Moreover, films of various sizes can be intermixed throughout the dual, horizontal belts for more convenient reading.

The viewer's independent belt system allows one belt to move while the other remains stationary. Thus, the radiologist can scroll through an unlimited number of the patient's earlier films while current films remain constantly in view. The vertical shades span the width of each light box, thus masking mammograms no matter where they're placed on the wide viewing area.

**Easy to learn and control.** The FlexiViewer's digital control panel has been arranged for effortless use. It includes belt action controls, Previous/Next buttons, buttons for adjusting luminance and the vertical shades and a Liquid Crystal Display. The integrated keypad provides a quick, efficient method for reading films that are not placed sequentially on the viewer. The LCD allows at-a-glance status of the luminance level and belt position. The standard Foot Switch provides a hands-free method of frame control. A unique RS232 interface is incorporated for upgrading to CAD.

### Specifications

Product Number .....	08-00976
Luminance .....	Exceeds ACR recommendations for reading mammography
Dimming .....	5 positions
Lamps .....	6 – 60-inch daylight fluorescent lamps per light panel; 50 Watts each
Viewing format .....	4-over-4 (14 x 17 inch); 6-over-6 (24 x 30 cm); 8-over-8 (18 x 24 cm)
Viewing area (WxH) .....	145 x 43 cm (57 x 17 inches) per belt
Films	
Transport mechanism .....	2 single-tier, horizontal belt; 50 frames each
Capacity, total .....	400–14 x 17 inch; 600–24 x 30 cm; 800–18 x 24 cm
Masking	
Vertical .....	One motorized shade (per tier); two programmable preset positions
Horizontal .....	Two manual shutters (left and right) per tier
Frame access	
Next/Prior .....	Standard buttons
Specific Frame Access .....	Numeric keypad integrated with control panel
Dimensions, in inches	
Shipping (WxHxD) .....	69 x 74 x 30, including casters
Operating (WxHxD) .....	69 x 74 x 42, including casters
Desk (WxHxD) .....	57 x 29 x 14
Depth of leg space .....	21
Weight .....	740 lbs.
Electrical .....	117 VAC, 60 Hz, 10 Amps
	Convenient 1 Amp (MAX) Accessory outlet
Color Temperature Rating .....	6,500 K
Maximum Heat Output .....	3,070 BTU/hr
Certifications/Listings .....	UL and Canadian UL



Technology

10625 Telge Road, Houston, TX 77095  
800-231-1747 281-815-1300 Fax 281-815-1494  
salessupport@radx.com www.ssxray.com